

SIGMA NEO 65

("Patent Pending")

NEW GENERATION INDUCTION SEALER



Maximum Line Speed

12 meter/min (* Depending on cap and bottle size)




Ultra Modern Sealing Head,

Seals from cap size 20 to 120mm



Security Protection and Alarm



Inbuilt Microprocessor Control



User Friendly



Single body mounting system



Stainless Steel Construction



Compact all-in-one design

ED^o - VANTAGES



Cost
Effective



Leak
Proof



Tamper
Evident



Assured
Quality



Environmental
Friendly



Higher
Productivity

ONLINE INDUCTION CAP SEALING MACHINE

Sigma Neo 65

Electronics Devices Worldwide Pvt.Ltd. launched innovative **IP 65 Controller** for induction cap sealing.

Sigma Neo Series is well know for its trouble free and reliable performance. Sigma Neo Series is designed to fit into most production lines without making modifications. The built-in castors provide added mobility to be moved from one line to another.

With over 20 years experience in the packaging industry, our R & D team has many opportunities to apply Induction Sealing Technology for various container shapes and sizes. As a result, customers can choose from a standard flat sealing head, tunnel sealing head or a customized sealing head for almost any closure design including CRC caps, Dome Caps, Sports Caps, Snap-On Caps, etc.

If you have a product filled in a container **NO MATTER WHAT SHAPE & SIZE, WE WILL SEAL IT** at your desired line speeds.

FEATURES

- ✓ Enclosure: Airtight, Watertight, Zero Ventilation
- ✓ Power Rating: 1.5 kW
- ✓ No under sealing or burning prospect.
- ✓ Improved distribution of reduced power loss.
- ✓ Innovative induction coil (head). Superior coil design to seal cap diameter 20 mm-120 mm
- ✓ The Maximum Conveyor Speed for sealing 12 meter/min (*Depending on Cap and Bottle Size)
- ✓ The Maximum Ambient temperature machine can be operated at 45° Celsius.



• Agro Chemical • Speciality Chemicals • Automotive • Dairy • Cosmetics • Dental • Pharmaceuticals • Food • Beverages • Water



Optional Accessories

- No Foil / No Cap Sensor
- Product Count / Reject count
- Jamming Timer
- Power save Timer
- Audio/Visual Alarm: 3-colour tower light with Buzzer
- Total Bottle counter
- Auto rejection system

Specifications

Input	230V ±10% V AC, Single Phase 50/60 Hz
Max.Line Speed	12meter/minute (*Depending on cap and bottle size)
Cap Size	20mm to 120mm
Net Weight	85kg
Dimensions	1650mm(H) x 755mm(W) x 895mm(L)